



## DEVIreg™ Smart

The DEVIreg™ Smart is an intuitive programmable timer thermostat to be connected to WIFI and DEVIsmart™ App controllable from anywhere, at any time. The thermostat is primarily used for controlling electrical floor heating elements. The thermostat is designed for fixed installation only and due to the special designed 2-part construction it fits a wide range of frames and sensors.

The DEVIreg™ Smart is fast and intuitive to setup using the App wizard. It has an open window detector and energy-saving program including an optimum start/end control ensuring the desired temperature at the correct time and thereby reducing the heating costs.

<b>Gross weight</b>	0.26 kg	<b>EAN</b>	5703466239636
<b>Net weight</b>	0.26 kg		
<b>Ambient temperature [°C] [Max]</b>	30 °C	<b>Sensor type</b>	Room + Floor
<b>Ambient temperature [°C] [Min]</b>	0 °C	<b>Software class</b>	A
<b>Ball pressure test temperature [°C]</b>	75 °C	<b>Standby power consumption [W] [Max]</b>	0.4 W
<b>Certification company</b>	CE EAC Intertek Semko	<b>Storage temperature [°C] [Max]</b>	65 °C
<b>Colour</b>	White RAL 9010	<b>Storage temperature [°C] [Min]</b>	-20 °C
<b>Depth [mm]</b>	44 mm	<b>Supply voltage range [V] AC</b>	230 V
<b>Description</b>	DEVIreg Smart pure white	<b>Supply voltage range [V] AC [Max]</b>	240 V
<b>DIN mounting</b>	No	<b>Supply voltage range [V] AC [Min]</b>	220 V
<b>Element IP Class</b>	21	<b>Temperature - floor [°C] [Max]</b>	45 °C
<b>Frost protection [°C]</b>	5 °C	<b>Temperature - floor [°C] [Min]</b>	5 °C
<b>Height [mm]</b>	85 mm	<b>Temperature - room [°C] [Max]</b>	35 °C
<b>Hysteresis (+/-)</b>	0.2	<b>Temperature - room [°C] [Min]</b>	5 °C
<b>Inductive load</b>	cos φ= 0.3 max 1A	<b>Temperature limiter [°C] [Max]</b>	45 °C
<b>Package depth [mm]</b>	110 mm	<b>Temperature limiter [°C] [Min]</b>	5 °C
<b>Package height [mm]</b>	84 mm	<b>Temperature max. limiter [°C] [Max]</b>	35 °C
<b>Package width [mm]</b>	108 mm	<b>Temperature max. limiter [°C] [Min]</b>	20 °C
<b>Pollution degree</b>	2	<b>Temperature min. limiter [°C] [Max]</b>	35 °C
<b>Product group</b>	Thermostats	<b>Temperature min. limiter [°C] [Min]</b>	10 °C
<b>Product name</b>	DEVIreg™ Smart pure white	<b>Terminal cable size max [mm<sup>2</sup>]</b>	2 x 2.5
<b>Regulation type</b>	Hysteresis	<b>Type</b>	DEVIreg™ Smart
<b>Relay switch</b>	1-pole	<b>Warranty [Year]</b>	5
<b>Resistive load max [A]</b>	16	<b>Width [mm]</b>	85 mm
<b>Sensor definition point [Ohm/°C]</b>	15kΩ / 25°C		