

DEVIreg™ thermostats selection guide

DEVIreg™ Opti



The DEVIreg™ Opti **electronic thermostat** is the combination of precise electrical underfloor heating control and elegant design. It is easy to install thanks to its preprogrammed settings. The open window function and low standby consumption will offer comfort with minimum stress on homeowner's wallet.

DEVIreg™ Touch



DEVIreg™ Touch is the intuitive floor heating thermostat with **touchscreen** operation. Compatible with a wide range of electric floor heating frames and sensors, and featuring an innovative 'click-fit' design, DEVIreg™ Touch provides a fast and flexible solution for almost any electric floor heating installation.

DEVIreg™ Smart



With DEVIreg™ Smart it's easy to adjust electrical underfloor heating from the smartphone. The intuitive DEVIsmart™ App turns the smartphone into a **remote control** and enables homeowner to easily operate underfloor heating system at home – from anywhere in the world.

 **EcoDesign**

Which DEVIreg™ electronic thermostat matches your needs?

Experience the combination of precise electrical floor heating and elegant design with our three different DEVIreg™ thermostats Opti, Touch, and Smart.

Advanced set-up wizard			✓
Remote control via Wi-Fi			✓
Android and iOS app available			✓
Living zones control			✓
Several masters for one system			✓
Multi-location control			✓
Automatic online software updates			✓
Advanced scheduling			✓
Set-up copying device to device			✓
Dimmer function			✓
Hex code-system		✓	✓
Touchscreen		✓	✓
Energy consumption monitoring		✓	✓
Intuitive programming		✓	✓
Multi-sensor compatibility		✓	✓
Forecast end fade out (adaptive end)		✓	✓
Forecast start function (adaptive start)		✓	✓
Multi-frame compatible		✓	✓
PWM regulation	✓	✓	✓
Low standby consumption	✓	✓	✓
ECO directive compliant	✓	✓	✓
Display set point temperature	✓	✓	✓
Display actual temperature	✓	✓	✓
Max and minimum floor temperature	✓	✓	✓
Childproof (safety lock)	✓	✓	✓
Battery back-up	✓	✓	✓
Open window detection	✓	✓	✓
Pre-programmed	✓	✓	✓
Digital timer	✓	✓	✓
Temperature range 5-35°C	✓	✓	✓
Floor temperature range 5-35°C (45°C after break out)	✓	✓	✓
Display	✓	✓	✓
3in1: Room sensor, floor sensor or room and floor sensor combined	✓	✓	✓
Programmable	Individual programming 2 periods/day (5+2 or 7 days)	Full flexible 2 periods programming	Full flexible 5 periods programming

DEVIreg™ Opti



DEVIreg™ Touch



DEVIreg™ Smart

